



APPLICABLE STANDARDS AND TESTS

- ✓ ASTM B-1, B-3, and B-8
- ✓ UL 83 and UL 1581
- ✓ Spark tested at 7500 VAC

VALUE ADD SERVICE

- ✓ Custom lengths and put-ups
- ✓ 12 available colors
- ✓ Wire paralleling and cabling
- ✓ Wire striping
- ✓ Custom print legends and labels

SCOPE

Single conductor Horizontal Directional Drilling (HDD) Wire is intended for use with locating systems by providing the electrical signal from the directional steering controls to the directional drilling bore head. It is suitable for lighting and power in industrial applications.

CONSTRUCTION

Conductors: The single conductors are solid or stranded annealed or hard uncoated copper.

Insulation: Concentrically applied PVC (polyvinyl chloride) insulation with a single layer construction. This eliminates the “balling” and joint breakage more typical of multi-layer constructions. Rated at -25°C to 75°C, 600V for wet or dry conditions.

IDENTIFICATION AND PACKAGING

The wire shall be identified by surface marking indicating the manufacturer and AWG size. 500 ft. and 2500 ft. spools are standard.

Custom lengths, non-standard colors, AWG and custom packaging are available by request.

AWG	Standard Number of Strands	Breaking Strength (lbs)	Insulation Thickness (inches)	Nominal Overall Diameter – Inches (standard strands)	Approx. Shipping Weight (Lbs/Mft)
10	7 / 19	310	.045	0.21 / 0.22	43
8	7 / 19	480	.045	0.24 / 0.24	67
6	7 / 19	760	.045	0.28 / 0.28	100



SNAP FOR MORE INFORMATION