

PET FENCE WIRE



APPLICABLE STANDARDS AND TESTS

- ✓ ASTM B-1, B-3, B-8 for Copper conductors
- ✓ ASTM D-1248 for Polyethylene
- ✓ ICEA S-70-547, ICEA S-61-402/NEMA WC5 and ICEA S-95-658/NEMA WC70 for cable construction
- ✓ UL 83, UL 1581 for tests and procedures
- ✓ Spark tested at 7500 VAC

VALUE ADD SERVICE

- ✓ Custom lengths and put-ups
- ✓ 12 available colors
- ✓ Wire paralleling and cabling
- ✓ Wire striping
- ✓ Custom print legends and labels



SNAP FOR MORE INFORMATION

SCOPE

Single conductor or multiconductor copper or copper clad steel, high molecular weight polyethylene (HMWPE) insulated pet containment specialty wire (also known as pet fence wire). HMWPE is a rugged and durable material considered excellent for moisture and abrasion resistance. This product is suitable for continuous service in direct burial, wet and dry locations, 75°C. Designed for use in electric pet fence systems or underground pet containment systems. Versions available in 30 volt or 600 volt.

CONSTRUCTION

Conductors: The single perimeter wire shall be solid or stranded, annealed or hard uncoated copper per UL83 and ASTM requirements. Multiconductor twisted shall be solid or stranded, annealed or hard uncoated copper per UL83 and ASTM requirements.

Insulation: Concentrically applied HMWPE insulation in accordance with UL83. LLDPE is standard and HDPE is available upon request.

IDENTIFICATION AND PACKAGING

Custom and standard print legends are available. 500 ft/spl. 1000 ft/spl, or 2500 ft/spl spools are standard, packaged and labeled with product name, description, AWG, and manufacturer. Standard 2" Lay for twisted wire.

Custom lengths, non- standard colors, Sunlight Resistance, AWG and custom packaging are available by request.

Copper	Breaking Pounds soft/ CCS	Bending Radius (inches)	Insulation Thickness (Inches) 30/600V	Nominal Overall Diameter (Inches)	Approx. Shipping Weight (Lbs/ Mft)	500' spl .030 .045	1000' spl .030 .045	2500' spl .030 .045
18	47/63	0.60/0.64	0.030/0.045	0.10 / 0.13	8/9: 7/9	6 ½ x 4 plastic	6 ½ x 9 plastic or metal	8 ½ x 7 8 ½ x 8 plastic or metal
16	74/99	0.68/0.68	0.030/0.045	0.11 / 0.14	12/14 : 10/13	6 ½ x 4 plastic 6 ½ x 6 plastic	6 ½ x 9 8 ½ x 7 8 ½ x 8 plastic or metal	12 x 6 wood or 10 ½ x 7 metal
14	124/161	0.72/0.72	0.030/0.045	0.12 / 0.15	18/20 : 15/18	6 ½ x 4 plastic 6 ½ x 6 plastic	6 ½ x 9 8 ½ x 7 8 ½ x 8 plastic or metal	12 x 10 plastic or wood
12	198/256	0.80/0.80	0.030/0.045	0.14 / 0.17	27/30 : 22/25	6 ½ x 6 plastic 6 ½ x 9 plastic	6 ½ x 9 8 ½ x 8 plastic or metal	12 x 10 14 x 10 plastic or wood

Twisted 2 Conductor Perimeter Wire (Standard 2" Lay)

Copper	Breaking Pounds soft/ CCS	Bending Radius (inches)	Insulation Thickness (Inches) 30/600V	Nominal Overall Diameter (Inches)	Approx. Shipping Weight (Lbs/ Mft)	500' spl .030 .045 2/C	1000' spl .030 .045 2/C	2500' spl .030 .045 2/C
18	47/63	0.60/0.64	0.030/0.045	0.10 / 0.13	8/9: 7/9	6½ x 9 plastic or metal	8½ x 7 8½ x 8 plastic or metal	12 x 10 wood or metal
16	74/99	0.68/0.68	0.030/0.045	0.11 / 0.14	12/14 : 10/13	8½ x 7 8½ x 8 plastic or metal	8½ x 7 8½ x 8 plastic or metal	12 x 10 14 x 10 plastic or wood
14	124/161	0.72/0.72	0.030/0.045	0.12 / 0.15	18/20 : 15/18	8½ x 8 10½ x 7 plastic or metal	10½ x 7 metal 12 x 6 wood	14 x 10 15 x 14 plastic or wood
12	198/256	0.80/0.80	0.030/0.045	0.14 / 0.17	27/30 : 22/25	10½ x 7 metal 12 x 6 wood	12 x 6 12 x 10 plastic or wood	20 x 10 Wood 3"arbor