


ALUMINUM TIE WIRE



APPLICABLE STANDARDS AND TESTS

- ✓ ASTM B-230 for an aluminum conductor
- ✓ ASTM D-1248 for Polyethylene
- ✓ ICEA S-70-547, ICEA S-61-402/NEMA WC5 and ICEA S-95-658/NEMA WC70 for cable construction
- ✓ UL 83, UL 1581 for tests and procedures
- ✓ Spark tested at 7500 VAC

VALUE ADD SERVICE

- ✓ Custom lengths and put-ups
- ✓ 12 available colors
- ✓ Wire paralleling and cabling
- ✓ Wire striping
- ✓ Custom print legends and labels
- ✓ Coils and reels available
- ✓ Alternate grade aluminum available



SNAP FOR MORE INFORMATION

SCOPE

Single conductor aluminum, high molecular weight polyethylene (HMWPE) wire used to secure the conductor to pin insulators on a distribution pole. HMWPE is a rugged and durable material considered excellent for moisture and abrasion resistance. This product is suitable for continuous service in direct burial, wet and dry locations, 75°C.

CONSTRUCTION

Conductors: Single aluminum conductors (grade 1350), solid per ASTM-230 requirements.

Insulation: Concentrically applied HMWPE insulation in accordance with UL83. LLDPE is standard and HDPE is available upon request.

IDENTIFICATION AND PACKAGING

Custom and standard print legends are available. Reels are packaged and labeled with product name, description, AWG, and manufacturer. Custom lengths, non-standard colors, Sunlight Resistance, AWG and custom packaging are available by request.

AWG	Insulation Thickness Mils	Nominal Overall Diameter – Inches	Approx. Shipping Weight (Lbs/Mft)
6	30 / 45	0.22 / 0.25	32 / 36
4	30 / 45	0.26 / 0.29	48 / 53
2	30 / 45	0.32 / 0.35	72 / 78