



APPLICABLE STANDARDS AND TESTS

- ✓ ASTM B-227, B-869, B-910/B-910M for Copper Clad Steel
- ✓ ASTM D-1248
- ✓ ICEA S-70-547
- ✓ ICEA S-61-402/NEMA WC5
- ✓ ICEA S-95-658/NEMA WC70
- ✓ UL 83 & UL 1581
- ✓ All products are spark tested at 7500 VAC

PRINT WHEEL

- ✓ KRIS-TECH WIRE CO #XX AWG CCS PE TRACER WIRE - DIRECT BURIAL USE ONLY
- ✓ KRIS-TECH WIRE CO #XX AWG CCS HDPE TRACER WIRE - DIRECT BURIAL USE ONLY

VALUE ADD SERVICE

- ✓ Custom lengths and put-ups
- ✓ 12 available colors
- ✓ Wire paralleling and cabling
- ✓ One Pull bundled wire solution
- ✓ Wire striping
- ✓ Custom print legends and labels

SCOPE

Single conductor copper clad steel, HMWPE (high molecular weight polyethylene) insulated tracer/locator wire. Together with the high strength of steel, the electrical and corrosion resistant properties of copper and the rugged properties of HMWPE this product is suitable for direct burial use in wet and dry locations, designed to carry an electrical signal for use in locating underground non-metallic pipe. Versions available in 30 volt, 600 volt and 1000 volt.

CONSTRUCTION

Conductors: The single conductors 21% conductivity copper clad steel, dead soft annealed (DSA), stress relieved (SR), high strength (HS) and extra high strength (EHS). Other conductivities and break strengths available by request.

Insulation: Concentrically applied HMWPE insulation in accordance with UL83. High Density HMWPE is available upon request.

IDENTIFICATION AND PACKAGING

Custom and standard print legends are available. 500 ft/spl. packed 4/box, or 2500 feet/spl spools are standard and packaged and labeled with product name, description, AWG, and manufacturer.

Custom lengths, non-standard colors, AWG and custom packaging are available by request.

AWG	Breaking Pounds DSA/SR/HS/EHS	Bending Radius (inches)	Insulation Thickness (Inches) 30/600/1KV	Nominal Overall Diameter – Inches	Approx. Shipping Weight (Lbs/Mft)
18	63 / 79 / NA / NA	0.64	0.030 / 0.045 / 0.060	0.10 / 0.13 / 0.16	7 / 9 / 12
16	99 / 125 / NA / NA	0.68	0.030 / 0.045 / 0.060	0.11 / 0.14 / 0.17	10 / 13 / 16
14	161 / 187 / 351 / NA	0.72	0.030 / 0.045 / 0.060	0.12 / 0.15 / 0.18	15 / 18 / 21
12	256 / 303 / 558 / 1185	0.80	0.030 / 0.045 / 0.060	0.14 / 0.17 / 0.20	22 / 25 / 29
10	408 / 473 / 887 / 1940	0.88	0.030 / 0.045 / 0.060	0.16 / 0.19 / 0.22	34 / 37 / 41
8	628 / 950 / 1005 / 2785	1.00	0.030 / 0.045 / 0.060	0.19 / 0.22 / 0.25	51 / 55 / 60



**SNAP FOR MORE
INFORMATION**