

DIRECT BURY LUG PLUS



FEATURES

- ✓ Waterproof and corrosion proof
- ✓ Install service line without cutting the main line
- ✓ One piece for easy installation
- ✓ Installs in one minute or less
- ✓ Designed for use with solid tracer wires
- ✓ Wire range from #14-8 Solid AWG Solid Copper
- ✓ #14-6 Stranded Copper
- ✓ #14-10 Steel Core Tracer Wire (CCS)
- ✓ High impact housing with user friendly design to prevent cuts or handling discomfort
- ✓ Use with low voltage tracer lines under 50 volts
- ✓ Pre-filled with silicone
- ✓ Approved for direct bury

KRIS-TECH CONNECTORS

Kris-Tech Insulation Displacement Connectors are used to install service lines without cutting the mainline. Waterproof and corrosion-proof, they install in one minute or less with no hand tools required.

PRODUCT SPECIFICATIONS & MEASUREMENTS

Max. Voltage	50V
Connector Size	1.18" x 2.04" x 2.57"
Wire Range	#14-8 Solid Copper
	#14-6 Stranded Copper
	#14-10 Steel Core Tracer Wire (CCS)
Conductor O.D. Range	.124" - .408"
Silicone Sealant Temperature Rating	-45°F to 400°F
Lug	Tin plated high conductivity aluminum
Screws	Zinc plated steel
Housing	High impact polypropylene
Sealant	Non-hardening viscous dielectric silicone