

INSULATION DISPLACEMENT



FEATURES

- ✓ Self Stripping- No Need to Strip Wires!
- ✓ Waterproof and corrosion proof
- ✓ No need to strip conductor
- ✓ Install service line without cutting the main line
- ✓ Installs with hand tools
- ✓ One piece for easy installation
- ✓ Installs in one minute or less
- ✓ Designed for use with solid/stranded copper and steel core tracer wire with .030" and .045" thick insulation
- ✓ Wire range from #14-12 Solid/ Stranded Copper
- ✓ #14-12 Steel Core Tracer Wire/CCS
- ✓ High impact housing with user friendly design to prevent cuts or handling discomfort
- ✓ Use with low voltage tracer lines under 50 volts
- ✓ Pre-filled with silicone
- ✓ Approved for direct bury

KRIS-TECH CONNECTORS

Kris-Tech Insulation Displacement Connectors are used to install service lines without cutting the mainline. Waterproof and corrosion-proof, they install in one minute or less with no hand tools required.

PRODUCT SPECIFICATIONS & MEASUREMENTS

Max. Voltage	50V
Connector Size	.96" x 1.73" x 1.78"
Wire Range	#14 - 12 Solid/Stranded Copper
	#14 - 12 Steel Core Tracer Wire/CCS
Conductor O.D. Range	121" - .166"
Silicone Sealant Temperature Rating	-45°F to 400°F